



- Setback and Clearance Notes**
- 1 To facilitate service and filter changes, maintain a clearance of 28" from STERN to nearest wall.
 - 2 To maintain good air circulation for cooling, please maintain a minimum of 2" from the Starboard, Port and Bow sides to nearest wall.

Materials Data

Dry Weight: 850 lbs (Without Lid)
Water Weight: 1243 lbs
Wet Weight: 2093 lbs (Without Lid)
Soft Spa Lid: 15 lbs
Tub: 14GA 304 Stainless Steel #4 Finish
Woodframe: Incense Cedar
Wood Sealer: Polyurea Poly Sealer ASTC Global 5500 EX
Plywood: Aquatek Meranti Fir Water-Proof Marine Plywood

Electrical Data

Voltage: 220 volts single phase
Frequency: 60hz
Amps: 50 amps
GFCI Trip Current: 4-6mA On-board GFCI

Mechanical Data

2 hp Dual Speed Pump Executive 56
Multi-Colored LED Lights
Plunges Time per Day: 270 minutes
Ambient Operating Temperature: : 15°F - 120°F
Water Temperature: 104°F
NEO 1500 Cont

Water Treatment

Total Water Volume: 149 gal
Disinfection: O₃
Pump: DC85E-24100S
Filter: 50sf Waterways (Chlorine Optional)
Ozone Injection Rate: 200mg/hr
Flowrate: 10 GPM
Turnover Rate: 15 min.

DISCLAIMER:

THE MOROZKO IS DESIGNED TO SUPPORT A HEALTHY LIFESTYLE, NOT DIAGNOSE, CURE, OR PREVENT SPECIFIC DISEASES OR MEDICAL CONDITIONS. MOROZKO HOT BATHS ARE NOT MEDICAL DEVICES, AND HAVE NOT BEEN EVALUATED BY THE FDA. MOROZKO MAKES NO CLAIMS OR WARRANTIES WITH REGARD TO THE HEALTH EFFECTS OF HOT PLUNGE THERAPY OR USE OF MOROZKO PRODUCTS. SEEK MEDICAL ADVICE FROM YOUR PHYSICIAN BEFORE EMBARKING ON A PROGRAM OF DELIBERATE HEAT EXPOSURE.

